

TECHNICAL DATA SHEET

Revision: 3

Edition: August/2022

STANLUX SILVER R 4850

- High performance aluminium paste with lamellar particles and narrow curve of particles size distribution
- Fine particles size
- Non leafing grade specially recommended for application in high performance systems that require differentiated metallic effect
- Solvent: mixture of White Spirit and High Aromatic

SPECIFIED CHARACTERISTICS

- | | |
|-----------------------------------|------------|
| • Solid content | 63% to 67% |
| • Maximum retention in # 325 Mesh | 0.10% |
| • Maximum water content | 0,15% |

INFORMATIVE CHARACTERISTICS

- | | |
|---|------------|
| • Average Particles Size- (D50 - Malvern) | 15 microns |
|---|------------|

Typical Uses

- Automotive coatings systems – OEM, refinishing and car parts
- Plastic coatings
- Metal effect coatings with very high surface requirements

Before using the product, we recommend that you consult the safety information, including the adequate handling and transport, which are available in the product's Material Safety Data Sheet – MSDS. The information mentioned in this technical bulletin represents our current level of knowledge and experience, but shall not be considered as a guarantee. It is the user's responsibility to assure the adequate use of the product, since **Aldoro** will not accept liability on any type of loss or damage which may arise due to the use of this information or application of the product. **Aldoro** reserves itself the right of changing, without prior notice, any data contained in this bulletin, resulting from adjustment, development or evolution of the production process.
